

### FUEL STORAGE SOLUTION FOR STORAGE TANKS & STATIONARY ENGINE APPLICATIONS

#### PRODUCT SNAPSHOT

##### UNIVERSAL FUEL ASSEMBLY

**Micron Rating:**  
R2721P - 20 micron (nominal)

**Max Flow Rate:**  
40 litres per minute (max.) at inlet pressure 20 kPa.

**Fuel Line Pressure:**  
Not to exceed 150kPa/21.8psi

**Inlet & Outlet Ports:**  
1" BSP

**Maximum Operating Pressure:**  
50°

Remote mounting head with 1" BSB inlet and outlet ports, plastic tool for replacement element change and filter element R2721P.

#### Purpose:

- Additional protection for diesel fuel delivery systems.
- Remove contaminants before it gets into your equipment fuel system.

#### Suitable for:

- Diesel Fuels

#### Applications:

- Low pressure/gravity fed bulk storage tanks in agricultural, construction and stationary engine applications.
- Ideal fuel storage solution.



#### R2721UA Inclusions

Product Image	Qty	Description
	1	Assembly: Cast alloy head, simple drain plug at the base of the plastic bowl
	1	Plastic tool for removing the plastic bowl.

Note: not all kit items are available for separate sale. Replacement cartridge filter R2127P available separately.